



P-SI STIMULATION SERVICE BULLETIN

9/93

P-SI (PETROCHEM - SCALE INHIBITOR)

GENERAL DISCRIPTION

P-SI is an amber liquid used to inhibit carbonate and sulfate scales in oil and water production and injection wells and equipment.

APPLICATION

P-SI is normally continuously injected at the wellhead or down the annulus for inhibition of a pipeline or down hole tubulars. It can also be squeezed in a formation for down hole inhibition or continuously injected into injection water. Treatment concentrations is normally 10-100 ppm, based on an evaluation of produced/injected water.

PHYSICAL PROPERTIES

Color	Amber liquid
Specific Gravity	1.052
Weight Per Gallon	8.77 PPG.
Flash Point	> 200 F (> 93.3 C)
Pour Point	< 18 F (< 7.8 C)
pH Neat	3.4

HANDLING AND SHIPPING

P-SI is a corrosive liquid. Avoid contact with eyes, skin or clothing. Use necessary personal protection. P-SI is shipped in 55-gallon poly drums.

SAFETY

Refer to P-SI Material Safety Data Sheet (MSDS)

Petrochem warrants ONLY title to product free from defects in workmanship and materials. There are no other warranties, expressed or implied. Liability and client's exclusive remedy is expressly limited to the replacement of such product on their return to Petrochem or at Petrochem's option, to the allowance of credit for the cost of such items; no special, incidental, indirect, punitive, or consequential damage liability is allowed.

This unpublished work is protected by copyright 1993. Petrochem, Inc. all rights reserved.