



P-AFA2

CEMENTING SERVICE BULLETIN

05/27/12

P-AFA2 (PETROCHEM – ANTIFOAM ADDITIVE 2/DEFOAMING AGENT)

TECHNICAL DATA

Petrochem De-Foaming agent P-AFA2 is designed for use in slurries that present foaming problems. It is most compatible with all classes of cement, cement extenders and Petrochem cement additives and do not change the slurry properties or the quality of the set cement.

P-AFA2 is designed to be blended with the cement or dispersed thoroughly in the water before mixing begins or directly to the slurry in the tub as needed. However, P-AFA2 has a greater capability as a De-Foaming agent when dry blended or added to the mix water.

P-AFA2 is normally used at concentrations of 0.2% by weight; however in some slurries a higher concentration may be necessary.

PROPERTIES

<u>PRODUCT</u>	<u>FORM</u>	<u>SP.GR.</u>	<u>PACKAGING</u>
P-AFA2	Tan Powder	1.5	50 Lb. /sack.

SAFETY

Chemical goggles is recommended while handling P-AFA2 De-Foaming agent since eye contact will result in irritation and could cause some injury to the eye. If the product gets in the eye/s, wash eyes with water (while holding open the eye lids) for 15 mins. then get medical attention. If skin contact is made, wash with soap and water.

Inhalation: if ill effects occur, remove person to fresh air and get medical attention.

Contaminated clothing is to be removed.